

# PrivacyMaster® (2" mesh — near total privacy)



**PrivacyMaster®** fence is a 2" chain link fence with unique Winged Slats "factory inserted" into the mesh. These specially designed "wings" provide a tight, snug fit in the chain link and offer approximately a 90 percent wind load and privacy factor (based on wire/mesh used-stretch tension). This fence provides the finishing touch to any property.

## **Benefits:**

- Superior privacy
- Cost-efficient solution for most settings
- Less installation time saves labor costs
- Low Maintenance
- Effective wind screen
- Enhances the appearance of the property
- Acts as exceptional sound barrier
- Virtually theft resistant
- Virtually unclimbable

## **Heavy-duty HDPE Slats**

**PrivacyMaster®** features strong and durable double wall slats "factory inserted" into the wire mesh. Choose from a wide variety of colors and styles. There's something just right for whatever your needs might be.

## **Galvanized Chain Link Fencing**

We fabricate our chain link mesh using only the highest grade 9 or 11 gauge galvanized wire. Our state-of-the-art manufacturing process ensures a consistent weave and product quality.

## **Vinyl Coated Chain Link Fencing**

We also offer a fused and bonded vinyl coated chain link mesh that is color coordinated to seven of our standard slat colors. And, we guarantee it for years of trouble-free use.

## **ASTM Designations**

Meets ASTM Designations (see chart on the next page)



# Technical Data

<b>PrivacyMaster® Specifications</b>	
Wind load and privacy factor - approximately (Based on wire/mesh used-stretch tension)	90%
2" x 2" Mesh	✓
Manufactured up to 12' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class V wire (2.0 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 8 gauge finish 9 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 9 gauge aluminized before weaving wire per ASTM A491, Type 1	✓
Self locking double wall slats without staples	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Fifteen year pro-rata limited warranty	✓

## Standard Wire Colors



## Standard Slat Colors



Colors are approximations. Exact representation of colors is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**



PrivacyMaster®'s double wall slats fit snugly into the galvanized steel or vinyl coated chain link mesh to provide 90% or near total privacy. They make an exceptional boundary for business complexes and residential property as well as providing outstanding security and beauty.



**MADE IN USA**

## HDPE Technical Properties

Property	Values
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70° F) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180° F) Under no stress, HDPE will not distort at this temperature
Strength	(4,000 psi) HDPE will not distort at lesser loads or impacts



## YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS AND ACCESSORIES FOR THE FENCE PROFESSIONAL!

**1.800.574.1076 • www.eprivacylink.com**