

# SlatLink® (2" mesh — semi privacy)



The central component of **SlatLink®** is the uniquely designed **FeatherLock®** slats. They are designed with a 10" self-locking section at the top of each slat that locks the slats tightly in position. Even though the bottom portion of the slat is thinner than the top, they still provide approximately 80 percent privacy (based on wire/mesh used-stretch tension). **SlatLink®** slats are "factory inserted" into the wire mesh.

### Benefits:

- Factory inserted slats
- Superior privacy
- Cost-efficient solution for most settings
- Less installation time saves labor costs
- Low Maintenance
- Effective wind screen
- Enhances the appearance of the property
- Acts as exceptional sound barrier
- Virtually theft resistant
- Virtually unclimbable

### Heavy-duty HDPE Slats

**SlatLink®** features strong and durable double wall slats "factory inserted" into the wire mesh. Choose from a wide variety of colors and styles. There's something just right for whatever your needs might be.

### Galvanized Chain Link Fencing

We fabricate our chain link mesh using only the highest grade 9 or 11 gauge galvanized wire. Our state-of-the-art manufacturing process ensures a consistent weave and product quality.

### Vinyl Coated Chain Link Fencing

We also offer a fused and bonded vinyl coated chain link mesh that is color coordinated to seven of our standard slat colors. And, we guarantee it for years of trouble-free use.

### ASTM Designations

Meets ASTM Designations (see chart on the next page)



# Technical Data

<b>SlatLink® Specifications</b>	
Wind load and privacy factor - approximately (Based on wire/mesh used-stretch tension)	80%
2" x 2" Mesh	✓
Manufactured up to 12' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class V wire (2.0 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 8 gauge finish 9 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 9 gauge aluminized before weaving wire per ASTM A491, Type 1	✓
Self locking double wall slats without staples	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Fifteen year pro-rata limited warranty	✓

## Standard Wire Colors



## Standard Slat Colors



Colors are approximations. Exact representation of colors is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**



**SlatLink®'s double wall slats snap into place because of the 10" self-locking section at the top of the slat. They provide 80% or semi privacy.**

## HDPE Technical Properties

Property	Values
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70° F) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180° F) Under no stress, HDPE will not distort at this temperature
Strength	(4,000 psi) HDPE will not distort at lesser loads or impacts



## YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS AND ACCESSORIES FOR THE FENCE PROFESSIONAL!

1.800.574.1076 • www.eprivacylink.com