



Safety Top Cap Lite™

The Safety Top Cap Lite™ is a lighter, more affordable version of our premium Safety Top Cap. It features a teardrop configuration and covers the exposed knuckles or barbs on the top of a chain link fence to protect against bodily injury. It also serves as a decorative trim piece to complement any galvanized or vinyl coated chain link fence.

Design – Durable, flexible plastic in an open teardrop shape.

Installation – Simply “snap” over the top of the fence and lock to the wire mesh with the zip ties (included with each package) through the four (4) pre-drilled holes in each slat.

Uses – Primarily used in a safety-yellow color for baseball outfields, but is also growing in popularity at all athletic fields, parks, playgrounds, and recreational facilities, as well as in residential and commercial applications.

Durability – Manufactured using HDPE plastic with UV stabilizers, Top Caps are designed to endure high impact and to resist the harmful effects of the sun and severe weather conditions for many years of continued use.


Limited Warranty – 15 years pro-rata

Cap Height	Width	Length	Pieces Per Bag	Coverage Area	Zip Ties
4"	2 1/2"	8 feet	10	80 linear feet	40 per bag

Standard Color (colors are approximations)



Safety Top Cap can also be specially ordered in these nine bright colors. Minimum quantities apply.



Exact representation of colors in printing is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**

HDPE Technical Properties

Property	Values
Melt Index	(.35) Optimum extrusion processing conditions for Fence Slats
Density	(.945) Polyethylene ranges anywhere from .914 to .960 in density
Minimum Temp.	(-70° F) Under no stress, HDPE remains flexible at this temperature
Maximum Temp.	(180° F) Under no stress, HDPE will not distort at this temperature
Strength	(4,000 psi) HDPE will not distort at lesser loads or impacts

Features and Benefits

Materials – SlatSource® caps are extruded from High-Density Polyethylene (HDPE), color pigments and ultraviolet (UV) inhibitors specially formulated to retard the harmful effects of the sun and lengthen the life of the caps.

Durability – This slat is designed to endure high impact, resist the harmful effects of the sun and to withstand severe weather conditions like salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance – Our slats are nearly maintenance free. They may be pressure cleaned of surface contaminants with plain water.

Wind Load Disclaimer – We will not be held responsible for fence damage resulting from wind load conditions due to insufficient structural support.

Designations – Meets ASTM Designation: F3000/F3000M



MADE IN USA



A PrivacyLink® Company

1.888.806.7528
www.eprivacylink.com
info@eprivacylink.com

Many patents and patents pending.